HVAC DISTRIBUTING LLC

ADVANTAGE SERIES
DUCTLESS SINGLE-ZONE MINI-SPLIT HEAT PUMP

AVAILABLE IN 9K–36K



ADVANTAGE SERIES

DUCTLESS SINGLE-ZONE MINI-SPLIT HEAT PUMP

UP TO 21.3 SEER2 / UP TO 7.5 HSPF2 / R-454B REFRIGERANT

- HIGH EFFICIENCY
- LOW AMBIENT COOLING
- 16 FT LINE SET INCLUDED
- TIMER
- SMARTPHONE APP
- LEAKAGE DETECTION
- FOLLOW ME FUNCTION
- LOW dBs
- GOLD FIN CONDENSER
- DC INVERTER

2 YEAR
COMPRESSOR WARRANTY

1 YEAR
PARTS WARRANTY

works with the Google Assistant

JUST ASK amazon alexa

MRCOOL® COMFORT MADE SIMPLE

V. 10.13.26

HVAC DISTRIBUTING LLC

ADVANTAGE SERIES SPECIFICATIONS

MODEL NO.		IDU	A-09-HP-WMAH-115D-O	A-12-HP-WMAH-115D-O	A-09-HP-WMAH-230D-O
		ODU	A-09-HP-C-115D-O	A-12-HP-C-115D-O	A-09-HP-C-230D-O
CAPACITY & PERFORMANCE					
Cooling Capacity		Btu/h	9000	12000	9000
	SEER2	Btu/w	21.5	21.2	21.2
	EER2	Btu/w	12.5	10.1	12.6
Heating Capacity		Btu/h	10000	12000	10000
	HSPF2-4	Btu/w	9	8.7	9.1
	HSPF2-5	Btu/w	7	6.7	7
Max Coverage Area		sq. ft.	Up to 400	Up to 550	Up to 400
Outdoor noise level (Hi)		dB(A)	52.5	54	53.5
ELECTRICAL					
Power Supply		V-Hz.Ph	115V-60Hz, 1Ph	115V-60Hz, 1Ph	208/230V-60Hz, 1Ph
Minimum Circuit (Disconnect)					
	Indoor	A	3	3	3
	Outdoor	A	18	19	12
Maximum Fuse (Breaker)					
	Indoor	A	15	15	15
	Outdoor	A	20	20	15
DIMENSIONS & WEIGHT					
Net Dimension (WxDxH)					
	Indoor	inch	28.43 x 7.36 x 11.42	31.57 x 7.44 x 11.69	28.43 x 7.36 x 11.42
	Outdoor	inch	30.12 x 11.93 x 21.85	30.12 x 11.93 x 21.85	30.12 x 11.93 x 21.85
Packing Dimension (WxDxH)					
	Indoor	inch	31.1 x 10.63 x 14.76	34.45 x 11.22 x 14.96	31.1 x 10.63 x 14.76
	Outdoor	inch	34.92 x 13.27 x 24.02	34.92 x 13.27 x 24.02	34.92 x 13.27 x 24.02
Net/Gross Weight					
	Indoor	lbs	17.42/22.93	19.4/25.13	16.98/22.27
	Outdoor	lbs	56.66/62.17	61.29/67.02	54.23/59.74

c ETL us
Intertek
5031495

AHRI CERTIFIED
www.ahridirectory.org
*Data provided by AHRI

All specifications are preliminary and are subject to change during mass production.

Equipment sizing and installation must be performed by a licensed HVAC contractor in accordance with ACCA Manual J and applicable local codes.

HVAC DISTRIBUTING LLC

ADVANTAGE SERIES SPECIFICATIONS

MODEL NO.		IDU	A-12-HP-WMAH-230D-O	A-18-HP-WMAH-230D-O	A-24-HP-WMAH-230D-O	A-36-HP-WMAH-230D-O
		ODU	A-12-HP-C-230D-O	A-18-HP-C-230D-O	A-24-HP-C-230D-O	A-36-HP-C-230D-O
CAPACITY & PERFORMANCE						
Cooling Capacity		Btu/h	12000	18000	24000	36000
	SEER2	Btu/w	21.3	19.2	18.7	18
	EER2	Btu/w	10.8	10.8	10.0	9
Heating Capacity		Btu/h	12000	18800	24000	36000
	HSPF2-4	Btu/w	9.1	9.6	9.3	8.5
	HSPF2-5	Btu/w	7	7.5	7.3	6.8
Max Coverage Area		sq. ft.	Up to 550	Up to 800	Up to 1050	Up to 1550
Outdoor noise level (Hi)		dB(A)	54	56	59.5	60.5
ELECTRICAL						
Power Supply		V~Hz.Ph	208/230V~60Hz, 1P	208/230V~60Hz, 1P	208/230V~60Hz, 1P	208/230V~60Hz, 1P
Minimum Circuit (Disconnect)						
	Indoor	A	3	3	3	3
	Outdoor	A	13	15	19	33
Maximum Fuse (Breaker)						
	Indoor	A	15	15	15	15
	Outdoor	A	15	20	20	35
DIMENSIONS & WEIGHT						
Net Dimension (WxDxH)						
	Indoor	inch	31.57 x 7.44 x 11.69	37.99 x 8.46 x 12.56	42.52 x 8.9 x 13.19	49.57 x 11.1 x 14.25
	Outdoor	inch	30.12 x 11.93 x 21.85	31.69 x 12.99 x 21.81	35.04 x 13.46 x 26.5	37.24 x 16.14 x 31.89
Packing Dimension (WxDxH)						
	Indoor	inch	34.45 x 11.22 x 14.96	41.14 x 12.01 x 16.14	45.47 x 16.34 x 12.6	52.76 x 17.72 x 15.16
	Outdoor	inch	34.92 x 13.27 x 24.02	36.02 x 14.57 x 24.21	39.17 x 15.67 x 29.13	42.91 x 19.68 x 34.84
Net/Gross Weight						
	Indoor	lbs	19.4/25.13	24.47/32.63	30.64/39.46	40.34/54.01
	Outdoor	lbs	59.08/64.37	72.31/78.48	94.58/102.29	150.35/160.27

c ETL us
Intertek
5031495

AHRI CERTIFIED www.ahridirectory.org
*Data provided by AHRI

All specifications are preliminary and are subject to change during mass production.

Equipment sizing and installation must be performed by a licensed HVAC contractor in accordance with ACCA Manual J and applicable local codes.