HVAC DISTRIBUTING LLC

OLYMPUS MULTI-ZONE SERIES

AVAILABLE IN 18K–48K





OLYMPUS E STAR® SERIES

SINGLE ZONE MINI SPLIT SYSTEM

JUST ASK amazon alexa

works with the Google Assistant

- LOW GWP R-454B REFRIGERANT
- DC INVERTER
- MULTI-ZONE FLEXIBILITY
- VERSATILE INSTALLATION
- SUPERIOR PERFORMANCE
- ENERGY EFFICIENT

7 YEAR
COMPRESSOR WARRANTY

5 YEAR
PARTS WARRANTY

HVAC-DISTRIBUTING.COM
1-855-HVAC-DIS 1-855-482-2347

MRCOOL® COMFORT MADE SIMPLE

V 10.09.26

HVAC DISTRIBUTING LLC

OLYMPUS E STAR® SERIES MULTI-ZONE SPECIFICATIONS

MULTI-ZONE CONDENSERS

HEAT PUMP CONDENSER - Outdoor Model		MULTI3-18HP230C-0	MULTI4-27HP230C-0	MULTI5-36HP230C-0	MULTI6-48HP230C-0
Maximum number of zones	UNITS	3	4	5	6
Power Supply	V~Hz, ph	208/230~60, 1	208/230~60, 1	208/230~60, 1	208/230~60, 1
SEER2	Btu/W	25.1	25.0	24.0	24.0
EER2	Btu/W	14.0	13.0	12.0	12.5
HSPF2-4	Btu/W	9.8	9.5	9.5	10.3
HSPF2-5	Btu/W	7.8	7.0	7.0	8.0
Minimum Circuit Ampacity	A	16	23	30.5	34
Maximum Fuse	A	20	25	35	40
Net Dimensions (WxDxH)	in	35.04 x 13.46 x 26.50	37.24 x 16.14 x 31.89	37.24 x 16.14 x 31.89	37.48 x 16.34 x 52.48
Packing Dimensions (WxDxH)	in	40.55 x 17.24 x 29.53	42.91 x 19.68 x 34.84	42.91 x 19.68 x 34.84	43.11 x 19.49 x 58.27
Net Weight	lbs	100.53	138.89	168.87	222.0
Outdoor Gross Weight	lbs	109.35	149.69	180.12	254.19

WALL MOUNTED AIR HANDLERS

WALL MOUNTED - Indoor Model		0-09-HP-WMAH-230C-0	0-12-HP-WMAH-230C-0	0-18-HP-WMAH-230C-0	0-24-HP-WMAH-230C-0
Power Supply	V~Hz, Ph	208/230~60, 1	208/230~60, 1	208/230~60, 1	208/230~60, 1
Minimum Circuit Ampacity	A	3	3	3	3
Maximum Fuse	A	15	15	15	15
Net Dimensions (WxDxH)	in	33.74 x 9.09 x 11.81	33.74 x 9.09 x 11.81	40.31 x 9.69 x 12.64	47.13 x 11.02 x 14.61
Packaging Dimensions (WxDxH)	in	36.22 x 12.20 x 14.57	36.22 x 12.20 x 14.57	43.11 x 12.80 x 15.75	50.39 x 14.17 x 17.91
Net Weight	lbs	23.37	22.93	27.34	43.65
Gross Weight	lbs	29.98	29.32	36.60	55.56
Indoor Noise Level	dB(A)	38 / 38 / 33 / 20.5 / 19.5	47 / 36.5 / 32.5 / 22 / 19.5	49.5 / 45.0 / 38.0 / 31.5 / 19.5	54.5 / 43.5 / 38.5 / 27 / 16
Piping Size Liquid Side/Gas Side	in	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"	3/8"-5/8"

CEILING CASSETTE

CEILING CASSETTE - Indoor Model		CASSETTE 09HP-230C-0	CASSETTE 12HP-230C-0	CASSETTE 18HP-230C-0	CASSETTE 24HP-230C-0
Power Supply	V~Hz.ph	208/230~60, 1	208/230~60, 1	208/230~60, 1	208/230~60, 1
Minimum Circuit Ampacity	A	3.0	3.0	3.0	3.0
Maximum Fuse	A	15	15	15	15
Net Dimensions (WxDxH)	in	22.44 x 22.44 x 9.65	22.44 x 22.44 x 9.65	22.44 x 22.44 x 9.65	22.44 x 22.44 x 9.65
Net Weight	lbs	35.27	35.27	35.27	47.18
Gross Weight	lbs	41.89	41.89	41.89	59.08
Piping Size Liquid Side/Gas Side	in	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"	3/8"-5/8"

CEILING DUCT AIR HANDLER

CEILING RECESSED - indoor model		DUCT 09HP-230B-0	DUCT 12HP-230B-0	DUCT 18HP-230B-0	DUCT 24HP-230B-0
Power Supply	V~Hz, P	208/230~60, 1	208/230~60, 1	208/230~60, 1	208/230~60, 1
Minimum Circuit Ampacity	A	3.0	3.0	3.0	3.0
Maximum Fuse	A	15	15	15	15
Net Dimensions (WxDxH)	in	27.56 x 19.92 x 7.87	27.56 x 19.92 x 7.87	34.65 x 26.54 x 8.27	39.37 X 29.53 X 9.65
Net/Gross Weight	lbs	39.46 / 46.74	39.46 / 46.74	54.45 / 66.14	80.47 / 91.93
Piping Size Liquid Side/Gas Side	in	1/4"-3/8"	1/4"-3/8"	1/4"-1/2"	3/8"-5/8"

c ETL us
Intertek
5029533

AHRI CERTIFIED www.ahridirectory.org
*Data provided by AHRI

All specifications are preliminary and are subject to change during mass production.

Equipment sizing and installation must be performed by a licensed HVAC contractor in accordance with ACCA Manual J and applicable local codes.

MRCOOL® COMFORT MADE SIMPLE