HVAC DISTRIBUTING LLC

VERSAPRO® SERIES
PACKAGE GAS ELECTRIC
AVAILABLE IN 24K–60K





VERSAPRO® SERIES
PACKAGE GAS ELECTRIC

UP TO 13.4 SEER2 / R-454B REFRIGERANT

LIFETIME
HEAT EXCHANGER WARRANTY

10 YEAR
PARTS WARRANTY

- INCLUDED LP CONVERSION KIT
- QUIET MULTI-SPEED BLOWER
- DURABLE BUILD & FINISH
- DIRECT SPARK IGNITION
- HIGH QUALITY HEAT EXCHANGER
- 81% AFUE
- CONVENIENT ACCESS PANELS
- HORIZONTAL OR DOWNFLOW INSTALLATION

MRCOOL® COMFORT MADE SIMPLE

V 10.14.26

HVAC DISTRIBUTING LLC

VERSAPRO® SERIES PACKAGE GAS/ELECTRIC SPECIFICATIONS

MODEL NO.		Unit	MPG24S060M013C	MPG30S060M013C	MPG36S090M013C	MPG42S090M013C	MPG48S090M013C	MPG60S110M013C
PERFORMANCE								
Power Supply		V-Hz, Ph	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1	208/230 ~ 60, 1
Cooling Capacity		Btu/h	22800	28400	34000	40000	47000	57000
	SEER2	Btu/W	13.4	13.4	13.4	13.4	13.4	13.4
Heating Input		Btu/h	60000	60000	90000	90000	90000	110000
	Output	Btu/h	48000	48000	72000	72000	72000	88000
Sound Rating		dB(A)	79	79	79	80	80	80
ELECTRICAL								
Min/Max Voltage		V	187/253	187/253	187/253	187/253	187/253	187/253
Max Current Ampacity (MCA)		A	18.8	21.5	25.2	29.9	36.4	41.4
Max Current Over Protection (MOP)		A	25	30	40	45	50	60
COMPRESSOR								
Rated Load Amps (RLA)		A	11	13	16	19	23	27
Locked Rotor Amps (LRA)		A	55	58	72	86	95	125
OUTDOOR FAN MOTOR								
Horsepower		HP	1/12	1/6	1/6	1/3	1/3	1/3
Full Load Amps (FLA)		A	0.8	1.0	1.0	1.9	1.9	1.9
Rated Airflow		CFM	2,144	2,909	2,909	5,223	5,223	5,223
INDOOR BLOWER MOTOR								
Horsepower		HP	1/2	1/2	1/2	1/2	3/4	3/4
Full Load Amps (FLA)		A	4.2	4.2	4.2	4.2	5.7	5.7
Rated Airflow @ .58 inwc		CFM	800	930	1050	1400	1700	1800
DIMENSIONS								
Net (WxDxH)		inch	50.6 x 35 x 46.4	50.6 x 35 x 46.4	50.6 x 35 x 46.4	51.5 x 44.8 x 49.7	51.5 x 44.8 x 49.7	51.5 x 44.8 x 49.7
Packing (WxDxH)		inch	51.4 x 37 x 48.6	51.4 x 37 x 48.6	51.4 x 37 x 48.6	52.1 x 45.2 x 52.3	52.1 x 45.2 x 52.3	52.1 x 45.2 x 52.3
Net Weight		lbs	422	432	444	539	560	562
Gross Weight		lbs	443	458	467	559	581	584
REFRIGERANT								
Refrigerant Type		Type	R-454B	R-454B	R-454B	R-454B	R-454B	R-454B
Refrigerant Charge		oz	42	44	46	60	60	60

c ETL us
Intertek
3124627

AHRI CERTIFIED® www.ahridirectory.org

*Data provided by AHRI

*All specifications are preliminary and subject to change during mass production.

Equipment sizing and installation must be performed by a licensed HVAC contractor in accordance with ACCA Manual J and applicable local codes.